

A METHOD FOR CALCULATION OF BI-DIRECTIONAL SOLAR PROPERTIES OF A VENETIAN BLIND

Nebojsa Stojanovic¹, D. Charlie Curcija²

¹DesignBuilder Software, d.o.o., 11000 Belgrade, Serbia

²DesignBuilder Software, Amherst, MA 01002, USA.

ABSTRACT

Venetian blinds are widely used as shading devices for windows. Methods for simulation of blinds are needed because measurements of their properties are expensive and quite involved. This paper presents novel method (named “directional diffuse method”) for calculation of bidirectional properties of a venetian blind. The shadowing of blind slat surfaces is taken into account during the calculation of the diffuse portion, resulting in a more realistic, non-uniform distribution of the scattered (diffuse) component. The method is applicable to devices with flat or curved slats. The resulting BTDF/BRDF can be used with the glazing layers BTDF/BRDF and full matrix calculation can be performed to get system performance with full spatial resolution. This methodology has been developed and implemented in the new version 6.0 of WINDOW program and has been successfully validated against limited amount of measurements and ray tracing simulations.

INTRODUCTION

Venetian blinds are widely used as shading devices for windows. Their purpose is to control solar heat gain, glare and privacy. There were number of studies where their performance had been measured, primarily in solar calorimeters and some with photogoniometers. Because of the need to do measurements at the real size, these measurements are expensive and quite involved.

Lately, there have been attempts to develop simulation methods, both simplified and with full complexity. Simplified method, involving diffuse reflection assumptions of the blind slats, has been developed and documented in ISO 15099 standard. While this method provides reasonable integrated performance for slats that are essentially diffusing, this methodology fails to provide spatial resolution that would be useful in daylighting and comfort applications. Also, treatment of diffuse reflections between venetian blind and layers of a glazing system is done in the same way as if they were specular reflections, which may introduce relatively larger errors when venetian blinds are calculated in conjunction with the attached glazing system.

CALCULATION METHOD

Directional diffuse method represents a novel approach in simulation of Venetian blind performance (DBS, 2006). Bidirectional properties of a venetian blind (BTDF and BRDF – Bidirectional Transmittance/Reflectance Distribution Function) are calculated. The blind slats are treated as purely diffusing surfaces, however, depending on the angle of the blind, the diffuse component is not constant in all directions, because of the shadowing of neighboring blind surfaces. This results in a better spatial resolution for daylighting and comfort calculations. The method is applicable to devices with flat or curved slats, and can be used for calculation of properties in any band of the solar spectrum.

Geometry of the Venetian blind is described in this model using following properties: Width of the slat (without curvature) [m], Distance between adjacent slats [m], Slat tilt angle [°], Radius of slat curvature [m] and number of slat segments. Slat material properties are: solar transmittance and front/back reflectances, and IR transmittance and front/back emissivities.




Figure 1. Diffuse Reflections in Venetian Blinds

Figure 1 shows the diffuse reflections and angles in the calculation of bi-directional transmittance of a venetian blind with curved slats. Each slat is divided into n number of linear segments. Incident beam radiation is coming from direction i, and is scattered along outgoing direction j. Unit irradiance at the front

surface of the blind (dotted vertical line on the left-hand side in Figure 1) is assumed. It is also assumed that incident radiation is repeatedly reflected in a diffuse manner off both slats, allowing the use of view factor based, gray body radiation calculation model (Siegel and Howell 1992). Calculation is performed in 2-D space, because incident irradiances at slat segments (E) and outgoing radiance of the blind essentially depend on the profile angles (ψ) of incident and outgoing directions. Diffuse radiosity leaving each slat segment (J) is calculated based on the geometry of the system and incident irradiance on irradiated segments (E). Radiation exchange between different slat segments is calculated using view factors between segments. The two imaginary surfaces on the left and right allow the use of enclosure radiation model, in which view factors are calculated using simple cross-string rule.

Outgoing radiance of the blind is calculated by summing up contributions from each slat segment visible from the outgoing direction of interest. Contribution of partially visible segments is proportional to the length of the visible part of the segment with respect to total segment length.

These calculations are performed for each incident and outgoing angle. In this model, also referred to as "Extended Basis", there are 145 incident and outgoing directions (Klems 2004). These results are placed in bi-directional transmittance function matrix (BTDF matrix), as (i, j) element. Directly transmitted part of incident radiation (which passes the blind without interaction with slat material) is calculated based on the geometry of the blind and incident profile angle, and it is added to element of the transmittance matrix which corresponds to that particular incident direction, and a collinear outgoing direction. Directly transmitted components are placed in the diagonal of the BTDF matrix. The reflected component is calculated in a similar manner, except that radiances are summed up on the same side as incident radiation. The results of reflectance calculations are placed in bi-directional reflectance Distribution Function (BRDF) matrix.

A total of 4 BTDF and BRDF matrices are obtained (2 for each side of the blind). The resulting BTDF/BRDF matrices can be used with the glazing layers bi-direction functions and full matrix calculation can be performed to get system performance with full spatial resolution. This methodology has been developed and implemented in the new version 6.0 of WINDOW program. Integrated (directional-to-hemispherical and diffuse) properties for a given Venetian blind are also calculated as one of by-products of this methodology.

SIMULATION RESULTS

A series of test simulations was run and compared to existing results. For these simulations, three types of materials for Venetian blinds, described in Annex C of ISO 15099 standard were used; A, B and C from Table 1.

A total of 4 blind configurations were used, with different tilt angle of flat slats: A45, B45, C45 and C80. Letters A, B and C indicate material used, followed by the slat tilt angle expressed in degrees. Simulation results were compared against two sources; 1) average results from ISO15099 and 2) results of detailed ray trace simulations. Directional-diffuse calculations were carried out for a set of 145 incident/outgoing directions (full basis in WINDOW 6.0 program).

Table 1. Solar properties of slat materials used

PROPERTY	A	B	C
Solar transmittance, τ_s	0.00	0.00	0.00
Solar reflectance outdoor (front) side, ρ_s^f	0.70	0.55	0.70
Solar reflectance indoor (back) side, ρ_s^b	0.70	0.55	0.40

Directional-diffuse calculation vs ISO15099

Table 2 presents results of these simulations, namely integrated, directional-to-diffuse solar transmittances and reflectances at normal incidence. *Ref* indicates reference values from ISO15099 and *DD* indicates results of directional-diffuse calculations.

Table 2. Selected calculated dir-dif properties at normal incidence

BLIND		A45	B45	C45	C80
Front transmittance	Ref	0.073	0.047	0.051	0.005
	DD	0.0730	0.0472	0.0508	0.0048
Back transmittance	Ref	0.288	0.216	0.271	0.027
	DD	0.2882	0.2161	0.2714	0.0268
Front reflectance	Ref	0.558	0.430	0.544	0.678
	DD	0.5587	0.4308	0.5454	0.6788
Back reflectance	Ref	0.103	0.066	0.070	0.273
	DD	0.1030	0.0661	0.0701	0.2735

Results of simulations show excellent agreement with results from ISO15099.

Directional-diffuse calculation vs TRACEPRO

A series of ray trace simulations for the four selected blind configurations were performed by LBNL (2006b) using TracePro program. In these simulations, a total of 200.000 rays per configurations were used, and thickness of the slat material was set to 0.01 mm.

Figures 2 to 4 present comparisons between directional-diffuse results (labeled Venetian) and ray trace results (labeled TracePro), for different profile angles of incident directions. Front and back transmittances and reflectances were compared for all test configurations, and they all show excellent agreement.




Figure 2 Front direct-to-hemispherical properties for configuration A45




Figure 3 Front direct-to-hemispherical properties for configuration B45




Figure 4 Front direct-to-hemispherical properties for configuration C80

CONCLUSION

Directional diffuse calculation method can be reliably used for predicting both integrated and localized performance of venetian blinds, for those materials that do not show substantial specularly.

Further work is needed to extend this methodology for specular surfaces.

ACKNOWLEDGEMENT

This work was supported through the grant from Lawrence Berkeley National Laboratory.

REFERENCES

- DBS. 2006 Technical report Calculation of Optical Properties for a Venetian Blind Type of Shading Device, DesignBuilder Software, 2006.
- ASHRAE. 2001. Handbook of Fundamentals, American Society of Heating, Refrigerating and Air-Conditioning Engineers, Inc. June 2001.
- IEA. 2000. Daylight in Buildings, A report of IEA SHC Task 21/ ECBCS Annex 29. International Energy Agency. July 2000.
- ISO. 2003. ISO 15099: Thermal Performance of Windows, Doors and Shading Devices – Detailed calculations. International Standardization Organization. 1st ed.. November, 2003.
- Klems, J.H. 1994. A New Method for Predicting the Solar Heat Gain of Complex Fenestration Systems I. Overview and Derivation of the Matrix Layer Calculation. ASHRAE Transactions V.100, Pt. 1.
- Klems, J.H. 2004. Angular Bases for Bi-directional Calculations, Interim report. Lawrence Berkeley National Laboratory, CA.
- LBL. 2006a. WINDOW 6.0: A PC Program for Analyzing Window Thermal Performance. Lawrence Berkeley National Laboratory. Berkeley, CA.
- LBL. 2006b. Interim report on the calculation of solar-optical properties of venetian blinds using TracePro. Lawrence Berkeley National Laboratory. Berkeley, CA.
- Siegel, R. and Howell, J.R. 1992 Thermal Radiation Heat Transfer, 3rd ed., Hemisphere Publishing