













Figure 8 The complete workflow of the development methodology

## CONCLUSION

The paper discovered quantified relationships between Applied Discharge Coefficients and geometrical parameters of different types of ventilation devices. It provides a guideline to build up virtual connection between systematic simulation (CONTAM) and CFD simulation (FLUENT), with the help of parametric modelling, statistics analysis and fitting tools, so that efficiency and accuracy can be ensured.

## REFERENCES

- Tan, Gang. and Glicksman L R (2005). Application of integrating multi-zone model with CFD simulation to natural ventilation prediction. *Energy and Buildings* 37(10), 1049-1057.
- Wang, Haojie. and Chen, Qingyan (2012). A new empirical model for predicting single-sided, wind-driven natural ventilation in buildings. *Energy and Buildings* 54, 386-394.
- Wang, Haojie. Karava P. and Chen, Qingyan (2015). Development of simple semiempirical models for calculating airflow through hopper, awning, and casement windows for single-sided natural ventilation. *Energy and Buildings* 96: 373-384.
- Dols, W S. and Polidoro, B J. CONTAM User Guide and Program Documentation Version 3.2. [1/9/2017]. <http://dx.doi.org/10.6028/NIST.TN.1887> : 55, 257-260.
- Zhou, J. Zhang, G. Xu, Y. et al (2006). Discussion on influencing factors of opening discharge coefficient in natural ventilation. *HV&AC* 36(12), 42-45
- Gong, Binbin. Gao, Hongbo. and Qian, Ji (2009). Effects of Greenhouse Side-window Opening Forms on the Value of the Flow Coefficient. *Journal of Anhui Agricultural Sciences* 37(20): 11-15
- Wang, Long. Pan, Yiqun. and Huang, Zhizhong (2012). Analysis of Influence Factors of Natural Ventilation Flow Coefficient of Exterior Window. *Building Energy Efficiency* 40(6): 12-14